

# ARGO Firefighting units

Firefighting units in conformity with EN 12845 standards for sprinkler and hydrants. Arrangement with one or two electrically-driven or engine-driven pumps, complete with jockey pump. VISION: special firefighting applications.

- End-suction back pull-out pumps with spacer coupling
- Components and accessories manufactured in full compliance with the EN 12845 standards
- Fire Technical Compartment available as option (compliant to Italian UNI 11292 standard only)

Model	Performance			
	Capacity	Head (max)	P (E)	P (M)
	m <sup>3</sup> /h	m	kW	kW
ARGO 32-160	21	38	3	4.6
ARGO 32-200	52	73	4 - 15	4,6 - 14,9
ARGO 32-250	50	98	7,5 - 18,5	7,8 - 18,8
ARGO 40-160	45	41	5.5	6.8
ARGO 40-200	87	74	7,5 - 18,5	7,8 - 18,8
ARGO 40-250	90	99	15 - 30	14,9 - 28,6
ARGO 50-160	69	41	7,5 - 9,2	7,8 - 14,9
ARGO 50-200	110	69	11 - 30	14,9 - 28,6
ARGO 50-250	108	109	22 - 55	28,6 - 53
ARGO 50-315	105	160	45 - 75	53 - 73,5
ARGO 65-200	150	69	15 - 37	14,9 - 37
ARGO 65-250	155	105	37 - 75	37 - 73,5
ARGO 65-315	150	151	75 - 110	73,5 - 110
ARGO 80-200	200	69	45 - 75	53 - 73,5
ARGO 80-250	210	95	55 - 90	53 - 110
ARGO 80-315	210	158	110 - 200	110 - 197
ARGO 100-250	280	103	55 - 110	53 - 145
ARGO 100-315	270	145	132 - 200	145 - 197
ARGO 125-250	420	105	90 - 160	110 - 164

\* max at NPSHr = 5m

(E): electric motor • (M): Diesel engine

